

Index

A

- AAR, *see* Association of American Railroads (AAR)
- ABAQUS FE rail modelling, 241
- ABAQUS software package, 89
- ABB, *see* ASEA Brown Boveri (ABB)
- AC, *see* Alternating current (AC)
- Acceptance tests, 24–25
- ADAMS, *see* Automatic Dynamic Analysis of Mechanical Systems (ADAMS)
- Adams/Controls plug-in, 253
- ADAMS/Rail software, 120;
see also Simulink
 - rail simulations, 120–121
 - for rail vehicle dynamics, 253–254
 - rail vehicle engineers using, 121
- Advanced simulation methodologies, 277;
see also On-line simulation
 - complex tasks and solutions, 277–278
 - real-time simulation, 300–308
- Aerodynamics, 88
- Air brakes, *see* Pneumatic brakes
- Air resistance, 191; *see also* Propulsion resistance
- Air spring, 13, 55, 63
 - elements, 111–112
 - installation, 60
 - secondary suspensions with, 111
 - suspension, 58, 60
- Alternating current (AC), 34
 - electric traction for AC locomotive, 73, 74
 - traction, 71–72
- American Public Transport Association (APTA), 23
- APTA, *see* American Public Transport Association (APTA)
- ASEA Brown Boveri (ABB), 30
- Association of American Railroads (AAR), 23
- Augmented formulation, 106–107
- Autocoupler, 21
 - draft gear in, 22
 - freight wagon, 21
- Automatic Dynamic Analysis of Mechanical Systems (ADAMS), 120, 253
- Autonomous rolling stock, 31
- Axle box, 17, 53, 54, 59
- Axle load, 32, 242

B

- Ballast, 203, 215–216
 - ballast–subballast pyramid submodel, 124, 214
 - damping coefficients of, 215
 - effects on vehicle dynamics, 92
 - vibration of, 214
- Bathtub, 10
- BCP, *see* Brake cylinder pressure (BCP)
- Beams on elastic foundation theory (BOEF theory), 203
- Bearing box, *see* Axle box
- Bearings, 15
 - axle box, 17
 - types, 17
 - wheelset, 16
- Bifurcation point, 231
- Bilevel car design, 36
- BOEF theory, *see* Beams on elastic foundation theory (BOEF theory)
- Bogies, 14, 52
 - centre-bowl, 14
 - FEM analysis, 15
 - heavy haul locomotive three-axle bogie, 54
 - monomotor, 55
 - passenger wagon, 14
 - radial steering of wheelsets, 74
 - rail vehicle bogie, 53
 - strain instrumentation, 4
 - three-piece bogie, 14
 - three-piece freight bogie, 15
- Bottom dump wagons, 9; *see also* Freight wagons
- Bounce test, 25; *see also* Curving test; Roll test; Twist test
- BPP, *see* Brake pipe pressure (BPP)
- Brake cylinder pressure (BCP), 152
- Brake cylinders, 18
- Brake modelling, 84
 - disc brakes, 88
 - ECP brakes, 87
 - pneumatic brakes, 85–86
 - wheel brakes, 87
- Brake pipe, 18
 - fluid models use, 86
 - models, 168, 169
 - pneumatic brakes, 85, 87
- Brake pipe pressure (BPP), 152

- Braking system, 18, 33, 67
 air brake delay, 20
 air brake system, 68
 artificially controlled resistance force, 67
 brake cylinder arrangements, 19
 characteristics, 75–76
 components of, 68–69
 DB system, 69
 electromagnetic brakes, 69
 electronic–pneumatic-type brakes, 20
 freight wagon brake cylinder, 19
 on freight wagons, 18
 heavy haul freight wagon, 19
 rail brake, 70
 types, 67
- Bridge modelling, 91
 gradual lead-in to bridges and culverts, 93
 rail stiffness, 92
 track pumping, 92
- Buckling effect, 179
- Bush element, 112
- C**
- Camborne road engine, 27
- Car bodies, 38, 51–52
- Cars, *see* Unpowered rail vehicle design
- Caterpillar Inc., 75
- CEM, *see* Crash energy management (CEM)
- CEN, *see* European Committee for Standardization (CEN)
- Centre, 1
- Centre for Railway Engineering (CRE), 1, 123
 active steering bogie, 6
 bogie rotation test rig, 2
 bogie strain instrumentation, 4
 data recorder, 6
 full-scale laboratory test, 3
 Heavy Testing Laboratory, 1, 2
 investigations, 3
 projects, 4
 solar cell, 5
 telemetry antenna, 5
 Wheelset-driven generator unit, 5
- Centre for Railway Engineering (CRE), 1, 123
 active steering bogie, 6
 bogie rotation test rig, 2
 bogie strain instrumentation, 4
 data recorder, 6
 full-scale laboratory test, 3
 Heavy Testing Laboratory, 1, 2
 projects, 4
 solar cell, 5
 telemetry antenna, 5
 theoretical and experimental investigations, 3
 Wheelset-driven generator unit, 5
- Centre for Railway Engineering—
 Longitudinal Train Simulator
 (CRE-LTS), 3, 123
- Centre for Railway Engineering—Three-
 dimensional Wagon–Track System
 Dynamics Model (CRE-3DWTSD
 Model), 123, 125
- Centre pivots, 64
 low-positioned centre pivot assembly, 65
 with spherical joints, 65, 66
 wheels in horizontal plane, 64
- Co-simulation interface design, 255
 client user interface settings, 273
 flow chart for, 258
 Gensys and Simulink implementation,
 269–275
 in GENSYS, 256–257
 in MATLAB, 257
 parameters for power car model, 269
 power car Gensys multibody model, 270
 power car simulation results, 274
 power car traction control system, 271, 272
 in Simulink, 257–269
 traction control subsystem for one axle, 273
 with TCP/IP, 256
- Co-simulation process, 249
 MATLAB/Simulink and multibody
 software packages, 250–255
 multi-disciplinary simulation, 250
 of whole system, 249
- CodeExport technique, 252
- Coil spring suspension, *see* Helical spring
 suspension
- Comfort ranking, 230
- Conicity, 16
- Continuous comfort, 229
- Conventional auto-couplers, 153
 conventional auto-coupler assembly, 153
 coupler slack modelling, 154
 linear wagon connection model, 156
 wagon connection model, 154, 155, 157–159
- Corrugation, 241
- Cosim_server 51717*, 256
- Coupler angles, 175, 176
 calculation, 178–179
 simulation results, 181
 for various vehicle combinations, 177
- Coupling, 20; *see also* Wagon
 free slack, 129, 162
 freight wagon autocoupler, 21
 freight wagon solid drawbar, 22
 longitudinal damping, 21–23
 mechanism, 21
 mechanism, 21; *also* Wagon
- Crash energy management (CEM), 18
- CRE, *see* Centre for Railway Engineering
 (CRE)

- CRE-LTS, *see* Centre for Railway Engineering–
Longitudinal Train Simulator
(CRE-LTS)
- Creepage, 205–208
- Critical speed, 25
- Curving performance, 236
 curving stability, 237
 horizontal and vertical curve
 negotiation, 236
 interlinked stages, 238
 limiting curves, 236
 limiting wheel lift ratios, 237
 twist test, 237
- Curving resistance, 140, 143
- Curving test, 25; *see also* Bounce test; Roll test;
Twist test
- D**
- D'Alembert's principle, 104–105
- Dampers, 61–62
- DB, *see* Dynamic braking (DB)
- DC, *see* Direct current (DC)
- Deep shelling, 239
- DEMU, *see* Diesel–electric multiple
unit (DEMU)
- Derailment, 224
 investigation, 115
 limiting L/V ratios, 225
 Nadal formula, 224–225
 ratio, 225
 simulation, 226, 227
 wheel–rail contacts, 228, 229, 230
 due to wheel flange climb, 224
- DHMU, *see* Diesel–hydraulic multiple
unit (DHMU)
- Diesel–electric locomotives
 manufacture, 28–29
- Diesel–electric multiple unit (DEMU), 42
- Diesel–hydraulic multiple unit (DHMU), 42
- Diesel locomotives, 38; *see also*
 Hybrid locomotives
 autonomous rail-powered vehicles, 38
 component for diesel–electric
 locomotive, 39
 electric power transmission, 41
 for heavy haul locomotive, 40
 power plant using, 39
 working principle, 38–39
- Diesel–mechanical multiple unit (DMMU), 42
- Diesel multiple unit (DMU), 42; *see also*
 Electrical multiple unit (EMU)
 categories, 42
 configuration application, 42
 for motorised passenger car, 43
 underframe power plant location, 44
- Diesel traction, 28–29
- Direct current (DC), 34
 DC traction, 71
- Disc brakes, 88; *see also* Wheel brakes
- Discretely supported model (DSM), 203
- DLL, *see* Dynamic Link Library (DLL)
- DMMU, *see* Diesel–mechanical multiple
unit (DMMU)
- DMU, *see* Diesel multiple unit (DMU)
- DOFs, *see* Six degrees of freedom (DOFs)
- Doubledeck coach design, 36
- Draft gear, 32, 153, 157
 drop hammer tests, 156
 friction-type draft gear unit, 153, 154
 polymer and elastomer draft gear units, 154
- Drawbars, 160–161
- Drive, individual, 41, 55
- DSM, *see* Discretely supported model (DSM)
- Dynamic braking (DB), 69, 134, 166
 characteristics, 137–138
 locomotive traction, 139–142, 145–148
 model, 136–142
 notch level, 134
 single vehicle model, 133
 systems, 69
 tractive effort performance curves, 135, 136
 tractive effort thermal derating curve, 135
 use, 136
- Dynamic clearance envelope calculations, 116
- Dynamic Link Library (DLL), 252
- Dynamic model elements, 94
- Dynamics, 104
 of bodies, 79
 bounce model, 80, 81
 D'Alembert's principle, 104–105
 equations, 106–8
 freight wagon model, 80
 Lagrange's equation, 105–106
 Newton–Euler equations, 104
 pitch model, 81
 rail vehicle, 79–82
 roll vibration mode, 81
 train, 82–83
- E**
- ECP brakes, *see* Electronically controlled
pneumatic brakes (ECP brakes)
- EDS, *see* Electrodynamic suspension (EDS)
- Elastic wheel, 57
- Electric locomotive, 29–30, 33
 brushless DC electric and AC motors, 36
 component locations for AC, 35
 electrical power supply system, 33
 electrification systems, 34
 non-autonomous locomotive, 33
 traction motors types, 35
 types, 34

Electrical multiple unit (EMU), 36
 under frame equipment locations, 37
 powered train, 36
 primary means of passenger transport, 38
 suburban trains, 37
 train configurations, 36

Electrical traction, 29–30

Electrodynamic suspension (EDS), 50

Electromagnetic brakes, 69

Electromagnetic suspension (EMS), 49

Electro-mechanical suspension, 61; *see also*
 Air spring suspension

Electronically controlled pneumatic brakes
 (ECP brakes), 87, 195

Elements, 108
 constraint elements, 112
 inertia elements, 109
 rail vehicle modelling axis system, 108
 suspension elements, 109–112

EMS, *see* Electromagnetic
 suspension (EMS)

EMU, *see* Electrical multiple unit (EMU)

Energy, 67, 69
 considerations, 191–192
 consumption, 193

Engineering analysis, 277

Euler equations, 104

European Committee for Standardization
 (CEN), 226

F

Fasteners, 203

Fatigue analysis, 82

Federal Transit Authority (FTA), 23

Field testing, 278

Finite element method (FEM), 88, 203
 analysis, 15
 and anti-ride-up device, 90
 insulated rail joint, 91
 meshed model examples, 91
 of rail, 90–91
 of rail vehicle structure, 89–90
 reducing modelling problem, 88
 time-dependent models, 88–89
 time-independent models, 88
 2D FEM, 89

Flanging, 15

Flat50-new rail, 232
 and ANZR1, ROA_worn and W_7
 wheel profiles, 232
 Flat50-new/ANZR1 contact, 234
 wheel–rail contact parameters for, 233

Flexi-coil suspension, 58; *see also* Air spring
 suspension

Fluid modelling techniques, 85

FRA, *see* Railroad Administration (FRA)

Freight rolling stock, 31
 formulas for propulsion resistance, 142
 propulsion resistance equations, 143

Freight wagons, 9, 80
 autocoupler, 21
 brake cylinder, 19
 braking system, 18
 general, 10, 11
 heavy haul, 9, 17, 19
 mixed, 18
 modern, 19, 21
 secondary suspension, 13
 solid drawbar, 22
 three-piece bogies in, 13, 14

FTA, *see* Federal Transit Authority (FTA)

G

Gas shock absorbers, 62

Gas turbine–electric locomotives, 45, 46

Gate turn off thyristors (GTO), 72

GENSYS software, 116
 bogie test rig model, 302
 co-simulation interface description,
 256–257
 multibody code, 299
 multibody model in, 282
 passenger car model, 118
 power car Gensys multibody model, 270
 pre-processors in, 117
 programs in, 116
 rail vehicle dynamic analysis
 applications, 117
 SIMFO-L taking lateral, 116
 SIMFO-V taking longitudinal, 116
 simulation results, 300
 track modelling in, 285

GETS, *see* Ground effect transport
 system (GETS)

GLPLOT program, 117

GPLOT program, 117

Gravitational components, 144
 brake vehicle model with grades, 145–148
 track grades, 144

Ground effect transport system (GETS), 77

Group drive, 41

GTO, *see* Gate turn off thyristors (GTO)

H

Hardware-in-the-loop simulation (HILS), 301

Heavy haul freight wagons, 9, 17–18
 brake equipment, 19

Heavy haul locomotive
 for dry friction condition, 286
 general arrangement for, 40
 primary suspension design, 59

- suspension design with flexi-coils, 59
 - three-axle bogie of, 54
 - Heavy haul trains, 195
 - control strategies, 166
 - dimensions of wagons, 177
 - hypothetical, 184
 - pushing limits of train design, 195–196
 - safe operation, 194
 - Helical spring suspension, 58; *see also*
 - Air spring suspension
 - Hertz static contact theory, 209
 - Heun method, *see* Runge–Kutta method
 - High-speed passenger train, 12
 - HILS, *see* Hardware-in-the-loop
 - simulation (HILS)
 - Hopper wagons, 9
 - Hose bag, 18
 - Hunting, 16, 206
 - Hybrid locomotives, 45, 48
 - advantages, 49
 - charge process, 45, 47
 - classification and mechanism, 47
 - disadvantages, 48
 - hybrid-powered freight train, 48
 - for switching operation, 47
 - Hybrid-powered freight train, 48
 - Hydraulic dampers, 62
 - Hydraulic suspension, 60–61
 - Hydraulic test equipment, 1
 - behaviours, 1, 3
 - bogie rotation test rig, 2
 - laboratory environment, 2
 - Hydraulic transmission, 41
- I**
- IGBT, *see* Insulatedgate bipolar transistors (IGBT)
 - Improved traction, 75–76
 - In-house packages, 123
 - CRE-3DWTSD model, 123–126
 - CRE-LTS, 123
 - longitudinal train modelling, 123
 - track model, 125
 - wagon model, 124
 - Inductrack suspension, *see* Permanent
 - magnets suspension
 - Inertia elements, 109
 - Insulatedgate bipolar transistors (IGBT), 72
 - International Organisation for
 - Standardization (ISO), 23
 - International Union of Railways (UIC), 23
 - Iron highway, 26
- J**
- Johnson–Vermeulen theory, 206, 208
 - Journal adapter, *see* Axle box
- K**
- Kalker's linear theory, 206, 208
 - Kinematics, 102
 - rigid-body, 102
 - spatial analysis, 104
 - velocity vector, 103
- L**
- Lagrange's equation, 105–106
 - Lateral instability, 231
 - bifurcation diagram, 231
 - Flat50-new-W_7 wheel–rail contact, 234, 235
 - rail profile, 232
 - three-piece wagon modelling, 232
 - wheel profile, 233
 - wheel–rail contact parameters, 233
 - Lateral/vertical wagon dynamics, 170; *see also*
 - Longitudinal train dynamics
 - longitudinal train interaction, 170
 - rollover on curves, 175–180
 - wagon body, 180, 182–186
 - wagon bogie pitch, 180, 182–186
 - wagon lift off, 186–188
 - wheel climb, 175–180
 - wheel unloading, 172
 - Leaf spring suspension, 58; *see also*
 - Air spring suspension
 - Linear wagon connection model, 156
 - Linkages, 67
 - LMAP, *see* Locomotive model acceptance
 - procedure (LMAP)
 - Loading gauge, 32
 - “Locomotion No 1”, 27
 - Locomotive bogie test rig model, 301
 - connections, 302, 303, 304
 - constraints on bodies, 302
 - in Gensys multibody software, 302
 - issues in, 304
 - parameters for, 303
 - wheelset, 304
 - Locomotive electric traction, 70
 - AC traction, 71, 72–74
 - DC traction, 71, 72
 - Locomotive model acceptance procedure
 - (LMAP), 242
 - Locomotives, 27
 - on bogie frame, 64
 - bogies, 52–54
 - brake system and devices, 67–70
 - Camborne road engine, 27
 - centre pivots, 64–66
 - components and systems, 51
 - design, 72–77
 - diesel–electric locomotive
 - manufacture, 28–29

- Locomotives, (*Continued*)
- diesel traction, 28–29
 - electrical locomotives, 29–30
 - electrical traction, 29–30, 70–72
 - frame and bogies connection, 64
 - frames and bodies, 51–52, 53
 - heavy haul locomotive three-axle bogie, 54
 - links and linkages, 67
 - magnetic levitation locomotives, 30
 - side bearers, 66
 - steam locomotives, 28
 - suspension system, 57–63
 - traction drives, 55–57
 - traction rods, 67
- Locomotive traction, 134
- notch level, 134
 - single vehicle model, 133
 - traction characteristics, 137
 - tractive effort performance curves, 135, 136
 - tractive effort thermal derating curve, 135
- Locomotive traction drives, 55
- design and parameters, 55
 - frame-mounted traction motor, 56
 - monomotor bogie, 55
 - providing independent rotation, 57
- Locomotive traction dynamic brake vehicle model
- with curves, 147, 148
 - with grades, 145, 146, 147, 148
- Simulation results, 140, 142
- in Simulink, 137, 138, 139, 141
- Long haul passenger wagon, 11
- Longitudinal comfort, 188
- passenger comfort acceleration limits, 190
 - passenger comfort displacement limits, 190
 - train accelerations, 189
- Longitudinal damping, 21
- draft gear impact, 22–23
 - by elastomeric elements, 21
- Longitudinal train, 170; *see also* Longitudinal train dynamics
- lateral/vertical wagon dynamics interaction, 170
 - modelling, 123
 - rollover on curves, 175–180
 - wagon body, 180, 182–186
 - wagon bogie pitch, 180, 182–186
 - wagon lift off, 186–188
 - wheel climb, 175–180
 - wheel unloading, 172
- Longitudinal train dynamics, 129
- design considerations, 195–196
 - energy considerations, 191–192
 - longitudinal comfort, 188–191
 - motions of rolling stock vehicles, 129
 - train control, 192–195
 - train management and driving practices, 192–195
 - train models, 130–133
- Longitudinal train dynamics simulation, 279; *see also* Real-time simulation
- in the CRE-LTS package, 280
 - track geometry for, 280
- Low-positioned centre pivot assembly, 65
- M**
- Magnetic levitation locomotives, 30
- Magnetic levitation train, 49
- advantages, 51
 - EDS principles, 50
 - EMS principles, 49
 - inductrack principles, 50
 - non-autonomous train, 49
- Mass elements, *see* Inertia elements
- MATLAB/Simulink software
- co-simulation with Multibody software packages, 250
 - Simpack, 251–253
 - Simulink, 251–253
 - universal mechanism, 254–255
 - Vampire and Simulink, 254, 255
 - VI-Rail and Simulink, 253–254
- MatSIM technique, 252, 253
- MBD, *see* Multibody dynamics (MBD)
- MBS, *see* Multibody simulation (MBS)
- mdlTerminate function, 268
- Modelling vehicle inputs, 133; *see also* Longitudinal train dynamics
- brake pipe and cylinder responses, 149
 - curving resistance, 140, 143
 - dynamic braking, 134–138
 - freight rolling stock, 142
 - gravitational components, 144
 - locomotive traction, 134–138
 - passenger rolling stock, 143
 - pneumatic brake models, 144, 146, 148–150
 - propulsion resistance, 138, 140
 - single vehicle model, 133, 134
 - three-vehicle ECP air brake model, 152, 153
 - three-vehicle train air brake model, 151
 - train air brake model, 152
 - train configurations, 161–162
 - train dynamics model development, 162–170
 - triple valve cylinder model, 149, 150
 - wagon connection models, 150, 153–161
- Modified Newmark- β method, 218–219
- MPLLOT program, 117
- MSC.ADAMS, 253
- co-simulation with Simulink, 254
- Multi-system performance, 29
- Multibody dynamics (MBD), 101, 120

- ADAMS/Rail, 120–121
 - benchmarks and comparisons, 126
 - dynamics, 104–108
 - elements, 108–112
 - GENSYS, 116–118
 - in-house packages, 123–126
 - kinematics, 102–104
 - NUCARS, 114–116
 - rail vehicle dynamics, 101
 - rigid body vs. flexible body, 112–113
 - SIMPACT, 121–122
 - software for rail vehicle dynamics, 113
 - subsystems collection, 101
 - UM, 122–123
 - VAMPIRE, 118–120
 - Multibody simulation (MBS), 121
 - Multibody software packages
 - co-simulation between MATLAB/Simulink, 250
 - Simpact, 251–253
 - Simulink, 251–253
 - universal mechanism, 254–255
 - Vampire and Simulink, 254, 255
 - VI-Rail and Simulink, 253–254
 - Multibody wagon model creation and verification, 280
 - constraints on bodies, 283
 - hypothetical track data, 281
 - lateral coupler force results, 281, 282
 - multibody model in Gensys, 282
 - time-stepping analysis, 285
 - track modelling in Gensys, 285
 - wagon modelling approach, 283
 - wagon subsystem parameters, 284
 - WMAP tests, 286
- N**
- Nadal formula, 224–225
 - Newton equations, 104
 - Newton–Euler equations, 104, 113
 - Nodes, 88
 - Non-autonomous rolling stock, 31
 - NUCARS, 114
 - general areas, 114–115
 - special areas, 115–116
 - Numerical integration methods, 216
 - comparison, 220–222
 - improved fourth-order Runge–Kutta method, 217–218
 - model parameters for examining solution techniques, 221
 - modified Newmark- β method, 218–219
 - numerical integrators, 95
 - Runge–Kutta–Fehlberg method, 222, 223
 - in time domain available, 217
 - 2D single wheel/single layer track model, 220
- O**
- On-line simulation, 278; *see also* Advanced simulation methodologies; Real-time simulation
 - adhesion and variable friction coefficients, 295
 - adhesion vs. longitudinal creepage, 294
 - constraints on bodies, 283
 - coupling elements, 298
 - and experimental data, 286, 289
 - FRA class 5 irregularities, 289
 - Gensys multibody code, 299
 - Gensys simulation, 300
 - hypothetical track data, 281
 - lateral coupler forces, 290
 - longitudinal train dynamics, 279–280
 - MATLAB, 294
 - maximum adhesion coefficient dependence, 297
 - multibody wagon model creation, 280–286
 - non-linear stability analysis, 288
 - parameters, 295, 296, 298
 - Polach's model, 289
 - results for model, 296
 - running safety simulation results, 291, 292, 293
 - simulation methodology, 278–279
 - train masses, 280
 - visual model check in Gensys GPLOT, 287
 - wagon dynamics simulation, 286, 289
 - wagon subsystem parameters, 284
 - wheel and rail profiles, 297
 - Ordinary differential equations (ODE), 251
- P**
- Pantograph modelling, 93
 - one-degree-of-freedom, 94
 - pantograph–catenary system, 93
 - Passenger car model, 118
 - Passenger rolling stock, 31
 - formulas for propulsion resistance, 143
 - Passenger wagon bogie, 14
 - Permanent magnets suspension, 50
 - PILS, *see* Processor-in-the-loop simulation (PILS)
 - Pneumatic brake models, 144, 146, 148; *see also* Dynamic braking (DB)
 - brake pipe and cylinder responses, 149
 - three-vehicle ECP air brake model, 152, 153
 - three-vehicle train air brake model, 151
 - train air brake model, 152
 - triple valve cylinder model, 149, 150

- Pneumatic brakes, 85; *see also* Wheel brakes
 - brake valve, 86
 - empirical lookup table, 85
 - train pneumatic brake model, 85, 86
- Pneumatic spring suspension, *see* Air spring suspension
- Polach model, 289
 - model parameters for adjustment, 305
 - Runge–Kutta method, 304, 305
 - variable friction coefficient in, 289
- Power braking, 129–130
- Power car
 - Gensys multibody model, 270
 - simulation results, 274
 - in Simulink, 272
 - traction control system, 271
- Powered rolling stock, 30, 31
- Powered traction vehicle, 51
- Processor-in-the-loop simulation (PILS), 301
- Propulsion resistance, 138, 140
 - freight rolling stock, 142
 - passenger rolling stock, 143
- Pulse width modulation (PWM), 72
- PWM, *see* Pulse width modulation (PWM)

R

- Rail brake, 70
- Rail Industry Safety and Standards Board (RISSB), 23
- Rail profile, 232, 233
- Rail ride comfort, 226, 228
 - comfort ranking, 230
 - continuous comfort, 229
 - standards, 226
- Railroad Administration (FRA), 23
- Rail track, 91, 201, 203
 - ballast, 203
 - classification, 204
 - gradual lead-in to bridges and culverts, 93
 - modelling, 92, 201
 - pumping, 92
 - rails support, 202–203
 - rail stiffness, 92
- Rail vehicle, 79, 101, 199, 200
 - analysis, 82
 - bogies classification, 200, 202
 - bounce model, 80, 81
 - freight wagon model, 80
 - as individual bodies, 79
 - modelling, 108, 199–201
 - pitch model, 81
 - roll vibration mode, 81
 - single wheel model, 202
- Rail vehicle modelling techniques, 79, 93
 - aerodynamics, 88
 - brake modelling, 84–88
 - bridge modelling, 91–93
 - dynamic model elements, 94
 - dynamics of bodies, 79–83
 - FEM, 88–91
 - insulated rail joint, 91
 - numerical integrators, 95
 - one-degree-of-freedom pantograph model, 94
 - pantograph modelling, 93
 - rail track, 91–93
 - rail vehicle modelling, 79
 - sub-structure, 91–93
 - wheel–rail contact patch, 83–84
- Rail vehicle–track interaction dynamics, 199
 - numerical integration methods, 216–222
 - rail track dynamics, 201–204
 - rail vehicle dynamics, 199, 200–201
 - vehicle acceptance simulations, 242–243
 - vehicle–track interactions, 238–242
 - wheel–rail contact modelling, 204–210
 - WTSD, 210–216
- Railways of Australia (ROA), 23, 233
- Rayleigh–Ritz method, 113
- RCF, *see* Rolling contact fatigue (RCF)
- Real-time simulation, 300
 - bogie test rig model, 302, 303
 - calculation time results for, 306, 308
 - constraints on bodies, 302
 - HILS approach, 301
 - linear approach, 308
 - longitudinal slips for, 307
 - parameters for Polach model adjustment, 305
 - simulation results, 305
 - traction control system, 306
 - wheel–roller contact implementation, 304
- Regenerative brake, 69
- REPOS, *see* Road Environment Percent Occurrence Spectra (REPOS)
- Rheostatic brake, 69
- RISSB, *see* Rail Industry Safety and Standards Board (RISSB)
- ROA, *see* Railways of Australia (ROA)
- Road Environment Percent Occurrence Spectra (REPOS), 3
- Rolling contact fatigue (RCF), 116, 238
 - categories, 239
 - cracks initiation and growth, 238
 - defects in rail, 239
 - reduction criteria, 240
 - shakedown diagram, 240
- Roll test, 24; *see also* Bounce test
 - Curving test; Twist test
- Rubber-absorbing elements, 62
- Rubber dampers, 62
- Rubber spring, *see* Side bearer pads
- Run-ins, 129
- Run-outs, 129

- Runge–Kutta–Fehlberg method, 217, 222, 223
 Runge–Kutta method, 82
 fourth order, 217–218, 222, 223
 for Polach model, 304, 305
- S**
- S-function mechanism, 257
 C-MEX Template file, 260
 client user interface for, 259
 macro substitutions, 260–269
- Series to parallel connection (SP connection), 71
- Shattered rims, 239
- Shear spring elements, 112
- Shelling, 239
- Shock absorbers, *see* Hydraulic dampers
- Shunting locomotives, 38
- Side bearers, 15
 constant contact, 15, 16
 types, 66
- Signalling and Safety system, 33
- Sills, 12
- SILS, *see* Software-in-the-loop simulation (SILS)
- SIMAT interface, 251, 252
- Simpack software, 121–122, 251–253
- Simulink software, 250–251
 co-simulation design interface in, 257
 in co-simulation mode, 251
 Gensys and, 267, 271
 with grades and curves, 147
 locomotive traction dynamic brake
 model, 139, 141
 S-function block in, 259
 SIMAT interface, 251, 252
 single vehicle model, 133
 three-vehicle ECP air brake model, 152
 three-vehicle train air brake model, 151
 three-vehicle train model, 163, 165, 171
 track grades with, 144, 145
 triple valve function, 148, 149
 Universal Mechanism and, 254, 255
 Vampire and, 254, 255
 VI-Rail and, 253
- Single vehicle model, 133
 simulation results, 134
 in Simulink, 133
- Six degrees of freedom (DOFs), 101, 104, 210
- Slack adjuster, 20
- Slackless packages, 160
- Slip controller, 272, 306
- Software-in-the-loop simulation (SILS), 301
- Solar cell, 5
- Spalling, 239
- Spatial analysis, *see* Three-dimensional analysis
- SP connection, *see* Series to parallel
 connection (SP connection)
- Standard gauge, 27
- Stephenson gauge, 27
- Stiffness element, 109
- Stringlining effect, 179
- Sub-structure, 91, 93
- Subballast, 203
 ballast–subballast pyramid submodel, 124, 214
 damping coefficients of, 215
 effects on vehicle dynamics, 92
- Suspension
 individual, 58
 passive, 62
- Suspension, active, 62
 actuators, 63
 functions, 62–63
 tilting suspension system, 63
- Suspension elements, 109
 bumpstop element, 109, 110
 damper element, 110
 friction element, 110, 111
 pinlink element, 111
 shear spring elements, 112
 stiffness element, 109
- Suspension system, 57; *see also* Brake system
 active suspension, 62–63
 air spring suspension, 58–60
 combinations of, 62
 dampers, 61–62
 electro-mechanical suspension, 61
 with flexi-coils, 59
 helical spring suspension, 58
 hydraulic suspension, 60–61
 leaf spring suspension, 58
 primary suspension design, 59
 of rail vehicles, 57
- Switchers, *see* Shunting locomotives
- T**
- Tank wagons, 11
- TCP/IP, *see* Transmission Control Protocol/
 Internet Protocol (TCP/IP)
- Telemetry antenna, 5
- Three-dimensional analysis, 104
- Three-dimensional wagon-track system
 dynamics (WTSD), 210
 track subsystem, 212–216
 wagon subsystem, 210–212
- Three-mass train model, 131
- Three-piece bogie, 13, 14, 199, 201
 freight bogie, 15
- Three-vehicle train model, 163
 air brake model, 151
 and brake system, 171, 172
 non-linear connections, 167
 simulation results, 164, 166
 with vehicle details, 165
- Time-dependent models, 88–89

- Time-independent models, 88
 - Tipler wagon, 10
 - Track brake, *see* Rail brake
 - Track component design, 115
 - Track gauge, 32
 - Track subsystem, 212
 - ballast and subballast, 215
 - comprises two rails, 212
 - dynamic equilibrium for track equations, 216
 - sleepers, 214
 - using Timoshenko beam theory, 213
 - Traction motors, 35
 - Traction rods, 67
 - Traction rolling stock, 30; *see also* Locomotives
 - absorbing device types, 32–33
 - designing limitations, 32
 - diesel locomotives, 38–41
 - DMU, 42–44
 - electric locomotive, 33–36
 - EMU, 36–38
 - gas turbine–electric locomotives, 45, 46
 - hybrid locomotives, 45–49
 - magnetic levitation train, 49–51
 - passenger rolling stock, 31
 - powered rolling stock, 30, 31
 - reduces shock loadings, 33
 - Tractive effort
 - characteristics, 272
 - maximum continuous, 135
 - performance curves, 135, 136
 - thermal derating curve, 135
 - Train control, 192
 - braking scenarios, 195
 - in-train forces, 194
 - mixed freight train, 193
 - parameters, 193
 - Train dynamics model development, 162
 - brake pipe model, 168
 - coupler slack effect, 164
 - coupling free slack, 162
 - dynamic brake, 166
 - simulation results, 169, 170, 173, 174
 - three-vehicle train model, 163, 164, 165, 171, 172
 - wagon connection model response, 167, 168
 - Train management and driving practices, 192
 - braking scenarios, 195
 - in-train forces, 194
 - mixed freight train, 193
 - parameters, 193
 - Train models, 82, 130, 132
 - differential equations system, 130
 - forces calculation, 133
 - linear wagon connection model, 131
 - longitudinal train model, 82, 83
 - non-linear modelling of system, 132
 - rolling resistance forces, 82
 - three-mass, 131
 - Transmission Control Protocol/Internet Protocol (TCP/IP), 251
 - architecture for co-simulation process, 256
 - MSC. ADAMS and Simulink co-simulation, 254
 - Twist test, 24, 237
 - 2D single wheel/single layer track model, 220
- ## U
- UIC, *see* International Union of Railways (UIC)
 - Underframe, *see* Wagon frame
 - Universal Mechanism (UM), 122 and Simulink, 254, 255
 - UM Loco, 122–123
 - Unpowered rail vehicle design, 9
 - acceptance tests, 24–25
 - advances in rail vehicle design, 26
 - bearings, 15–17
 - bogies, 14–15
 - braking system, 18–20
 - constant contact side-bearer, 16
 - coupling, 20–23
 - passenger wagon bogie, 14
 - standards, 23–24
 - suspension elements, 13–14
 - three-piece bogie friction wedges, 14
 - wagons, 9–12, 17–18
 - wheelset, 15–17
- ## V
- Vactrains, *see* Vacuum train
 - Vacuum train, 77; *see also* Magnetic levitation train
 - VAMPIRE software, 118, 254, 255
 - and GENSYS126
 - pre-and post-processors in, 119
 - VAMPIRE Pro, 119
 - wagon model with three-piece bogies, 120
 - Vehicle certification, 115
 - Vehicle Design Optimisation, 114–115
 - Vehicle dynamic performances, 224; *see also* Rail vehicle–track interaction dynamics
 - curving performance, 236–238
 - derailment, 224–226
 - lateral instability, 231–235
 - rail ride comfort, 226, 228–230
 - Vehicle ride quality, 115
 - Vehicle–track interactions, 238
 - rail and wheel wear, 240–241

- RCF cracks initiation and growth, 238–240
- rolling contact fatigue, 239
- shakedown diagram, 240, 242

- W**
- W_7 profile, 233
- Wagon, 9
 - bathtub gondola-type coal, 10
 - components, 9, 10
 - dynamic model, 182
 - frame, 11–12
 - freight container, 11
 - high-speed passenger train, 12
 - long haul passenger, 11
 - model, 124
- Wagon bodies, 17–18, 180
 - compressive coupler forces, 184
 - coupler forces, 185
 - operational data, 184
 - selected axle force data, 187
 - for train trip simulations, 182
 - wagon dynamic model, 182
 - zoom-in on axle force data, 186, 187
- Wagon bogie pitch, 180
 - compressive coupler forces, 184
 - simplified wagon pitch models, 183
 - with three pitch motions, 182
- Wagon connection models, 150, 154, 155
 - auto-couplers and draft gear packages, 153–159
 - drawbars, 160–161
 - mild impact loading, 158
 - non-linear connection, 168
 - passenger and freight wagon draft gears, 159
 - shunt impact, 158
 - slackless connection, 160
 - slackless packages, 160
 - slow loading, 157
- Wagon lift off, 186
 - coupler forces, 188, 189
 - train simulation results for coupler forces, 187
 - wagon pitch model, 188
- Wagon model acceptance procedure (WMAP), 242, 279
- Wagon subsystem, 210
 - force–displacement relationships, 212
 - suspension force, 211
 - wagon model, 211
- WEL, *see* White etching layer (WEL)
- Wheel and rail profile, 84, 297
- Wheel and Rail Profile Design Optimisation, 115
- Wheel-burns, 238
- Wheel brakes, 87
- Wheel climb, 175
 - coupler angles, 175, 176
 - coupler angles calculation, 178–179
 - coupler angles for vehicle combinations, 177
 - quasi-static bogie, 179, 180, 181, 182
 - simulation results, 181
 - train with remote-controlled locomotives, 178
- Wheel profile, 233
- Wheel–rail contact modelling, 204
 - Cartesian coordinate system, 205
 - creepage, 205, 207
 - using Hertz static contact theory, 209, 210
 - Kalker's linear theory, 206, 208
 - rail, 207
 - single-point contact, 209
 - wheelset coordinate system, 206
- Wheel–rail contact patch, 83
 - contact force, 84
 - modelling rail vehicles, 83
 - multiple-point wheel–rail contact model, 85
 - railhead surface fatigue cracks, 84
 - two-point contact and angle of attack, 84
- Wheel–rail lubrication studies, 115–116
- Wheelset, 15, 41, 109, 211, 304
 - bearings, 16, 17
 - coned, 205
 - conicity, 16
 - coordinate system, 206
 - lateral displacement, 234
 - mass, 80
 - wheel profile, 16
 - wheelset-driven generator unit, 5
- White etching layer (WEL), 239
- Wind loading, 93
- Wind overturning, 25
- WMAP, *see* Wagon model acceptance procedure (WMAP)
- WTSD, *see* Three-dimensional wagon-track system dynamics (WTSD)